Evidence of Performance

Fire resistance of door and shutter assemblies

Test Report

22-001831-PR01 (PB-C04-01-en-01)

DOM Sicherheitstechnik GmbH & Co. KG Wesselinger Str. 10-16 Client 50321 Brühl (Germany)

Product	Single-leaf fire-resistant door assembly	
Designation	"H3-1 OD"	
Overall dimensions of assembly (W x H)	1,189 mm x 2,156 mm	
Clear opening (W x H)	1,043 mm x 2,083 mm	
Material	Sheet steel door with	
	Steel corner frame	
Type of opening	Side hinged door	
Special features	Electronic hardware "DOM ENIQ Guard", Slimline	
Exposed face	Opening face	
Supporting construction	Standard supporting construction, rigid construction of high density and a thickness of 175 mm	



Fire resistance

Criteria	Test results
E - flame > 10 s	40 minutes
E - gap gauge	40 minutes
E - cotton pad	40 minutes
I ₁ - insulation	22 minutes
I ₂ - insulation	40 minutes
W - radiation	-
Termination of test	in the 41st minute

ift Rosenheim 23.05.2022

Translation dated 30.05.2072

Anyke Aguirre Cano, Dipl.-Ing. Head of Testing Department Fire safety

Überwachungs- und Zertifizierungsstelle Fire Safety

This document is valid without a signature. The original document n° 22-001831-PR01 (PB-C04-01de-01) dated 23.05.2022 remains legally binding.

posenhein

Notifizierte Prüf-



Basis

EN 1363-1:2020 EN 1363-2:1999 EN 1634-1:2014+A1:2018 EN 16034:2014 EN 13501-2:2016

Equivalent to the national DIN EN standard/s.

Basic test report of ift Rosenheim 22-001665-PR02 (PB-C04-01-de-01) 04.05.2022

Representation



Instructions for use

This test report serves to demonstrate the fire resistance of door and shutter assemblies. This test report does not provide any verification of applicability as set out by the Building relevant Control Authorities!

Validity

The data and results given refer solely to the tested and described specimen. Testing for fire resistance does not allow any statement to be made on any further characteristics regarding performance and quality of the construction submitted.

Notes on publication

The ift Guidance Sheet "Conditions and Guidance for the Use of ift test reports" applies. The cover sheet can be used as an abstract.

Contents

The report comprises a total of 40 pages (incl. Annexes)

- Object
- Procedure
- 3 Results

Annex (33 pages)

*



