

DOM Guard S: Orderform

Amount					
Typ			Slimline 	Wideline 	Wideline with rosettes 
System	ENiQ 13,56 MHz				
	ELS 125 kHz				
	DOM Tapkey 13,56 MHz				
Model	Set (Outside & Inside)*				
	Without interior fitting				
Cylinder-punch hole OUTSIDE	Europrofile	70 mm			
		72 mm			
		78 mm			
		85 mm			
		88 mm			
		90 mm			
	Without (Blind)	70 mm			
		72 mm			
		78 mm			
		85 mm			
		88 mm			
		90 mm			
		92 mm			
Cylinder-punch hole INSIDE	Europrofile	70 mm			
		72 mm			
		78 mm			
		85 mm			
		88 mm			
		90 mm			
	Without (Blind)	70 mm			
		72 mm			
		78 mm			
		85 mm			
		88 mm			
		90 mm			
		92 mm			
Handles	Mitre	U-Shaped			
		L-Shaped			
		Cranked			
	Curved	U-Shaped			
		L-Shaped			
		Cranked			
Ball Handle outside					
Antibacterial coating					
Lock-spindle	7 mm				
	8 mm				
	8,5 mm				
	9 mm				
	10 mm				
Door Thickness	Long shield Inside	Rosettes Inside			
	28-38 mm	31-41 mm			
	38-48 mm	41-51 mm			
	48-58 mm	51-61 mm			
	58-68 mm	61-71 mm			
	68-78 mm	71-81 mm			
	78-88 mm	81-91 mm			
	88-98 mm				

! * The classification as a protective fitting with corresponding attack resistance only applies in conjunction with the associated interior fittings (set).

Client name

Customer number

Commission number

Offer/object number

Date/Signature/Company stamp