

SKG-IKOB PRODUCTCERTIFICATE

442.393.02

Date of issue: 27-05-2020



Certificate holder

DOM Sicherheitstechnik GmbH
Wesseling Straße 10-16
D-50321 Brühl
T: +49 (0) 2232 704 435
E: Info@dom-sicherheitstechnik.de
I: www.dom-sicherheitstechnik.com



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

euro profile cylinder_ with non lockable knob

delivered under logo / brand:

DOM

delivered under type- and / or article number:

333 K Diamant

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A handwritten signature in blue ink, consisting of a stylized, cursive script.

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

CERTIFICATE

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

SKG-IKOB PRODUCTCERTIFICATE

DOM Sicherheitstechnik GmbH
Number: 442.393.02

page 2 of 2

1. PRODUCT

euro profile cylinder_ with non lockable knob

PRODUCT TYPE

cylinder

2. TECHNICAL SPECIFICATION

Operating: Mechanical operation
Construction: double, with push-knob OR standard knob
System: round key profile: 1 row of 21 mechanical operated rotating of which
of 10 functional
Material: cylinder body: sintered steel with steel bridge
Dimension: 17 mm profile from 30 mm in various extensions per 5 mm
Fixing: 1 steel bolt M5, length \geq backset + 10 mm
Intended use: in combination with cylinder mortice locks and security furniture.
Pay Attention:
This cylinder achieves only the SKG-star rating if
a door element (including side window), wherein [mr] at least P4A laminated glass has been applied, OR
in a door element (including side window) with
a section filling without a view on the knob.

A wooden door element (including side window) with
a view to the "standard" turning knob, should be
provided with a SKG (V) certified anti-drill / manipulation device

3. DELIVERY

The delivery includes an installation instruction:
Version 1.3 + care instruction 1-5-20

4. PERFORMANCES

A euro profile cylinder_ with non lockable knob according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this euro profile cylinder, with non lockable knob is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this euro profile cylinder, with non lockable knob is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).
