



Technical Data

ENiQ Guard®

Guard Versions:



Guard Slimline Width: 40 mm

- Length: 253.0 mm
- Height: 20.0 mm
11.5 mm

Guard Wideline Width: 56 mm

- Outside cover, without handle
- Inside cover, without handle

Guard Compact Versions:



Guard Compact Slimline Width: 40 mm

- Length: 133.0 mm
72.0 mm
56.0 mm
- Height: 20.0 mm
11.5 mm
8.0 mm

Guard Compact Wideline Width: 56 mm

- Outside covers and inside cover Slimline, without cylinder rose
- Cylinder rose Slimline
- Cylinder and handle rose Wideline
- Outside cover, without handle
- Inside handle covers, without handle
- Cylinder roses

Technology:

- 13.56 MHz Mifare
- 2.4 GHz (BLE: Bluetooth Low Energy)

Interaxis dimension:

(distance handle ↔ cylinder)

- Guard: Between 55 and 92 mm
- Guard Compact: ≥ 64 mm Slimline
≥ 56 mm Wideline

Application:

- Electronically controlled handle on the outside
- Interior handle is always operable
- Suitable for doors with high frequency of use and frequent violent usage
- Category of use: grade 4 according to EN 1906 / EN 16867

Installation:

Different installation types

- Screwing through the door from the inside
- Screw-on installation

Door leaf thickness:

- 36-106 mm, increment in 10 mm steps



Technical Data

ENiQ Guard®

Fixation points:

- Adjustable by vertically movable threaded sleeves or screws
- Guard:

- Upper fixation point:	min. 65.0 mm	max. 84.0 mm
- Middle fixation point:	min. 21.5 mm	max. 25.0 mm
- Lower fixation point:	min. 112.0 mm	max. 139.0 mm
- Guard Compact:

- Upper fixation point:	min. 65.0 mm	max. 84.0 mm
- Middle fixation point:		21.5 mm
- Wideline:	Horizontal distance of fixation points	38.0 mm
- Slimline:	Vertical distance of fixation points	50.0 mm

 Adapter plate for threads with 50 mm distance available

Backset:

- Slimline versions (width of escutcheon 40 mm):
For backset < 25 mm the application has to be checked
- Wideline versions (width of escutcheon 56 mm):
For backset < 35 mm the application has to be checked

Handle types:

L-shape U-shape cranked ball



Max. dimensions: Height (incl. cover) x Width (only handle)

Outside	86.3x130 mm	86.3x 40 mm	97.8x160 mm	114.3x80.6 mm
Inside	78.3x130 mm	78.3x140 mm	89.8x160 mm	

- Handle can be adjusted to DIN-L/DIN-R doors on site

Handle spindle:

- 9 mm (with adapters 7 / 8 / 8.5 / 10 mm are possible)

Handle movement:

- Maximum angle: 45°, upward handle movement possible
- Rest position can be corrected by $\pm 7^\circ$

Durability:

- ≥ 200.000 cycles (grade 7 of EN 1906 and EN 16867)

Environmental influences:

- Temperature: -25°C to +65°C
- Relative humidity: 20% to 99%, no condensation
- Anticorrosive according to DIN EN 1670 class 3 (salt spray test, 96 hours), grade 3 according to EN 1906
- Protection class: IP 54 (PIV test report no. 44-7/19)
- Not suitable for permanent outdoor use
- Environmental resistance according to grade 4 of EN 16867



Technical Data

ENiQ Guard®

Approvals and certifications:

- Technical approval (abZ) granted by DIBt (German technical authority), approval no. Z-6.100-2554
 - Suitable for the usage in single- and double-leaf fire and smoke control doors made of wood, aluminium and steel
 - Suitable for the usage in escape and emergency routes
- Suitable for doors in escape in panic routes
 - Tested as emergency exit device for escape routes according to EN 179, Test report 123000167.01/02 of MPA NRW (Germany)
Classification according to EN 179:2008: 3-7-7-B-1-3-5-2-A-B
 - Test of compatibility to panic exit devices operated by a horizontal bar in preparation (according to EN 1125)
- Suitable for use on fire resistance and smoke controlled doors, grade B according to EN 16867 (PIV test report no. 57-4/19)
- Hardware performance sheet (HPS) for building hardware according to EN 16035 (ift no. 20-001125-PR01 / KB-G10-UZ05)

- Tested according to EN 16867 (PIV test report no. 57-4/19)

prEN 16867	1 Category of use	2 Durability	3 Door mass	4 Fire & smoke doors	5 Safety	6 Environmental resistance	7 Credential related security	8 Security: Attack resistance	9 Security: Related to EN1906
grade	4	7	-	B	1	4	D	0	0

EN 1906	1 Category of use	2 Durability	3 Door mass	4 Fire & smoke doors	5 Safety	6 Corrosion resistance	7 Security: Attack resistance	8 Execution type	-
grade	4	7	-	B	1	3	1	A	

Surface and colours:

- All visible metal parts: satin stainless steel
- Plastic cover:
 - signal white (similar RAL 9003)
 - jet black (similar RAL 9005)
 - graphite grey (similar RAL 7024)

Signalling:

- Optical signalling by 4 multicolour LEDs (moving light effect)
- Additional acoustic signalling (can be disabled)

Clutch duration:

- Adjustable ranging from 1 to 30 seconds
- Permanent open/close mode, Office function

Power supply:

- 2 pcs. Lithium AAA cells, 1.5 Volts
- Recommended battery: Energizer Ultimate Lithium
- Correct operation is not guaranteed for other battery types



Technical Data

ENiQ Guard®

Battery life time and data preservation:

At room temperature (+20°C):

- Up to 70.000 locking cycles or
- Up to 3 years stand-by time in case of non-use or
- Up to 2.5 years by typical 10 locking cycles per day

Intelligent battery management:

- Multilevel temperature compensated battery warning system
- 10 year data preservation without battery

Time / Date:

- Buffering during battery change: typically 1 minute
- Clock drift at room temperature: ± 10 minutes/year
at -25°C and +70°C: -50 minutes/year

Programming:

Programming via NFC/BLE-with the following prerequisites:

- ENiQ App (NFC/BLE) (see datasheet ENiQ App)
- ENiQ Software via BLE Stick (see separate datasheet of ENiQ AccessManagement Software)
- Storage of max. 5 programming cards

Events:

- Ring buffer for the latest 2.000 events

Inductive transponder interface:

- Reading range: up to 3 cm
- Frequency: 13.56 MHz
- Field strength in 10 m distance: < 42 dB μ A/m
- In conformity with ETSI EN 300 330

- Supports passive transponders (ISO 14443 A)

- Encryption: Mifare DESFire EV1/EV2/EV3: AES-128 Bit
Mifare Classic: Crypto-1
- Additionally AES-128 Bit encryption with object specific keys

Bluetooth Low Energy (BLE):

- Communication range: typical 15 m
- Frequency: 2.4 GHz
- Transmission power: < 20 dBm
- Conformity to ETSI EN 300 330

- Key exchange: Curve25519-256 Bit (elliptical curve)
- Encryption: XSALSA20-256 Bit
- Signature / Authentication: Poly1305-128 Bit
- Bluetooth version: 5.0 (\geq Firmwareversion 4.3)

Transponder types:

- DOM Standard Tag, Premium Plus Tag, ClipTag
- ISO card transponder
- Other types have to be checked

Storage of access authorisations in the device:

- Supported transponders:
 - Mifare DESFire EV1/EV2/EV3 2k, 4k, 8k
 - Mifare Classic 1k, 4k
 - Mifare Plus S/X 2k, 4k
 - Mifare Ultralight / Ultralight C

- Storage of maximal 5.000 authorisations in the device
- Identification of the transponders by their UID or by other unique data



Technical Data **ENiQ Guard®**

Storage of access authorisations on the transponders:

- Supported transponder types:
 - Mifare DESFire EV1/EV2/EV3 2k, 4k, 8k
 - Mifare Classic 1k
- Other data on the transponder:
 - „Blacklist“ with blocked transponders
 - Authorisation period, weekly schedule at the device

Weekly and day’s schedules:

- Storage of max. 256 weekly / day’s schedules per device
- Each weekly schedule points to 10 arbitrary day’s schedules (7 week days and 3 special days for holidays):

1	2	3	4	5	6	7	8	9	10
Mon	Tue	Wed	Thu	Fri	Sat	Sun	holiday / vacation		
DS1	DS2	DS3	DS4	DS5	DS6	DS7	DS8	DS1	DS2
- Each day’s schedule consists of 96 time slots of 15 minutes, in each case definable as authorised or unauthorised:

0 ⁰⁰	1 ⁰⁰	2 ⁰⁰	3 ⁰⁰	...	20 ⁰⁰	21 ⁰⁰	22 ⁰⁰	23 ⁰⁰
█	█	█	█	...	█	█	█	█
- access rights of the weekly / day’s schedules:
 - # 0: no access (unauthorised)
 - # 1: access with no time-limits, active special functions may limit access
 - ## 2-254: freely definable
 - # 255: access with no time-limits, active special functions are ignored
- Permanent-open and permanent-close weekly schedules
- Office function

Holidays:

- Storage of maximum 256 holidays or vacation periods per device
- Definition of 3 different kinds of holidays/vacations
- Begin / end as from / to date



All data correspond to the actual development status and are subject to change at any time without notice.

